

alsecco Alsispray MATT Plus

SPRAY FORMULATED INTERIOR MATT PAINT

| | |
|--|---|
| Field of Application | AlsiSpray MATT-Plus is premium quality, scrubbable paint suitable for interior walls & ceilings. AlsiSpray MATT-Plus is high opacity and offers the highest coverage and workability with good filling properties. AlsiSpray-Matt-Plus is scrub resistant / wet abrasion Class 2. AlsiSpray MATT-Plus is formulated for use with the Nespray or other airless spray machines. |
| Pack Size | 15l, 25l (25l white only) |
| Composition | Polyvinyl acetate resin dispersion, poly-siloxane, titanium dioxide, silicates, water, additives and preservatives |
| Colour Range | White / tinted colours available |
| Optimum Coverage | 120ml/m ² - 175ml/M ² per coat on smooth substrates, the exact rate of consumption is best established by a trial coating. |
| Application | Brush, Roller, Airless Spray, Nespray machine Airless application a 213-519 tip at 2000 psi, medium to course filter For Nespray application, use twin-tips provided. |
| Drying Times | Under Normal Conditions recoatable 4-6 hours Completely dry in 3 days Lower temperatures will extend drying times. Do not apply under +5°C |
| Storage | Keep paint cool but frost free |
| Thinner /cleaner | Water |
| Thinning | Regular application: add up to max. 1 part water to 20 parts paint Sealing new surfaces: add up to max. 1 part water with 10 parts paint Regular airless spray application: add up to max. 1 part water with 5 parts paint Nespray application: use undiluted |
| Properties | Unique Nespri-Tec mist-free application Excellent opacity/coverage High filling properties Solvent-free Low odour Water-Thinnable Ecologically compatible Easy to apply Matt finish |
| Characteristics to DIN EN 13 300: | Wet abrasion class 3 (DIN 53 778) Opacity (hiding, covering power) Class 1 - highest rating available |
| Substrate Preparation | Make sure all surfaces are clean and free from loose or flaking coatings or other contaminants before application. |

| | |
|---|---|
| <p>Ensure new surfaces are fully dry.</p> | <p>AlsiSpray MATT-Plus will adhere to most surfaces without a primer, but if unsure always try a test area before application. Clean or sand surfaces prior to application as necessary. Fill surface defects prior to application using a proprietary filler. For further details of substrate pre-treatment, please contact Alsecco Technical assistance.</p> |
| <p>Unsuitable substrates</p> | <p>Do not apply direct to distemper paints, if unsure always try a test area before application. Heavily stained areas may require suitable primer before AlsiSpray MATT-Plus may be applied (Water stains, nicotine, soot).</p> |
| <p>System Information</p> | <p>Stir thoroughly before use. The recommended process to achieve premium finish is 2 coats of AlsiSpray MATT-Plus. However for pre-coated surfaces a single coat may be sufficient.</p> |
| <p>Health and Safety Information</p> | <p>Ensure the area is well ventilated during application and drying. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with clean cold water. If irritation persists consult your GP. Remove paint from skin using soap and water. When spraying, avoid breathing spray mist. Wearing of a suitable mask or respiratory device is advised during application. Minimum recommended respiratory protection: to BS Advice (technical assistance) If you require any more information please contact Alsecco Technical helpline on the details below.</p> |
| <p>Customer service number</p> | <p>01785 818998</p> |
| <p>Email</p> | <p>interior.technical@alsecco.co.uk</p> |
| <p>Website</p> | <p>www.alsecco-interiors.co.uk</p> |
| <p>Issued</p> | <p>January 2010</p> |