

# alsecco Alsispray MATT

## SPRAY FORMULATED INTERIOR MATT PAINT

<b>Field of Application</b>	AlsiSpray MATT is premium quality paint suitable for regular interior walls & ceilings. AlsiSpray MATT is high opacity and offers the highest coverage and workability with good filling properties. AlsiSpray MATT is formulated for use with the Nespray or other airless spray machines.
Pack Size	15l, 25l (25l white only)
Composition	Polyvinyl acetate resin, titanium dioxide, calcium carbonate, silicates, water, additives and preservatives
Colour Range	White / tinted colours available
Optimum Coverage	120ml/m <sup>2</sup> - 175ml/m <sup>2</sup> per coat on smooth substrates, the exact rate of consumption is best established by a trial coating. .
Application	Brush, Roller, Airless Spray, Nespray machine Airless application a 213-519 tip at 2000 psi, medium to course filter For Nespray application, use twin-tips provided.
Drying Times	Under Normal Conditions recoatable 4-6 hours Completely dry in 3 days Lower temperatures will extend drying times. . Do not apply under +5°C
Storage	Keep paint cool but frost free
Thinner /cleaner	Water
Thinning	Regular application: add up to max. 1 part water to 20 parts paint Sealing new surfaces: add up to max. 1 part water with 10 parts paint Regular airless spray application: add up to max. 1 part water with 5 parts paint Nespray application: use undiluted
Properties	Unique Nespri-Tec mist-free application Excellent opacity/coverage High filling properties Solvent-free Low odour Water-Thinnable Ecologically compatible Easy to apply Matt finish
<b>Characteristics to DIN EN 13 300:</b>	Wet abrasion class 3 (DIN 53 778) Opacity (hiding, covering power) Class 1 - highest rating available
Substrate Preparation	Make sure all surfaces are clean and free from loose or flaking coatings or other contaminants before application. Ensure new surfaces are fully dry. AlsiSpray MATT will adhere to most surfaces without a primer, but if unsure always try a test area before application. Clean or sand surfaces prior to application as necessary. Fill surface defects prior to application using a proprietary filler. For further details of substrate pre-treatment, please contact Alsecco Technical assistance.



Unsuitable substrates	Do not apply direct to distemper paints, if unsure always try a test area before application. Heavily stained areas may require suitable primer before AlsiSpray MATT may be applied (Water stains, nicotine, soot).
System Information	Stir thoroughly before use. The recommended process to achieve premium finish is 2 coats of AlsiSpray MATT. However for pre-coated surfaces a single coat may be sufficient.
<b>Health and Safety</b>	Ensure the area is well ventilated during application and drying. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with clean cold water. If irritation persists consult your GP. Remove paint from skin using soap and water. When spraying, avoid breathing spray mist. Wearing of a suitable mask or respiratory device is advised during application. Minimum recommended respiratory protection: to BS EN 149:2001, FFP3 Keep out of reach of children.
Disposal:	Do not empty waste material into water courses or drains. In site conditions, do not empty onto the ground. Materials and all related packaging must be disposed of in a safe and preferably environmentally friendly manner. Dispose fully in accordance with local authority guidelines.
EU limit value:	Category (a/A): max g/l (2010). This product contains <g/l of VOC
Advice (technical assistance)	If you require any more information please contact Caparol Technical helpline on the details below.
Customer service number	01785 818998
Email	interior.technical@alsecco.co.uk
Website	www.alsecco-interiors.co.uk
Issued	January 2010