

# Top Primer P

Pigmented synthetic-resin bonded primer paint for decorative plasters

**Areas of application** | Primer to match the colour and improve adhesion before the final coat of synthetic-resin and mineral plasters. Suitable for interior and exterior applications.

**Product properties**

- Absorbency-regulating
- Water-vapour permeable
- Water-repellent
- Acts as coupling agent
- Adhesion-improving
- Enhanced texturing of subsequent decorative plasters
- Surface provides a good grip, since it is filled with quartz
- Results in optimum and economical application of the decorative plaster

**Technical data** | Binder base | Terpolymer synthetic-resin dispersion

Specific gravity | approx. 1,7 g/cm<sup>3</sup>

**Application instructions** | Substrate pre-treatment

- All substrates must be sound, even, clean and free from adhesion-reducing residue.
- Apply Sub Primer HT to substrates that need to be stabilised.

Mixing | Ready for application  
Can be thinned with 20 % water max.

Application

- Apply by brush, roller or as a spray.
- Use short-pile rollers to ensure an even application.

Consumption | approx. 200 - 250 ml/m<sup>2</sup>  
Determine the exact amount of material required by coating a test area on site.

Information about the weather | The temperature must not fall below + 5 °C during application and drying.

Drying time | approx. 2 - 6 hours  
Dependent on temperature and relative humidity

Cleaning of tools | With water while product is still fresh

Application by machine | Please ask for our special information sheet on machine application.

<b>Packaging</b>	Article number	02041
	Packaging unit	PP tub 15 l
	Colour	Natural white and pigmented in shade of subsequent plaster coating
<b>Other information</b>	Transport	Not a hazardous product
	Storage	Minimum storage life of 1 year if kept cool, protected against frost and in the original sealed packaging.
	Information on safety	We will be pleased to provide the EC safety data sheet on request.