

# Top Primer Si

Pigmented, silicate-bonded primer paint for silicate-based decorative plasters

<b>Areas of application</b>	Primer paint to match the colour and improve adhesion before the final coat of silicone-resin plasters. Suitable for interior and exterior applications.	
<b>Product properties</b>	<ul style="list-style-type: none"> <li>■ Water-vapour permeable</li> <li>■ Acts as coupling agent</li> <li>■ Adhesion-improving</li> <li>■ Absorbency-regulating</li> <li>■ Reduces the risk of colour variations in the subsequent application of pigmented silicate plasters</li> <li>■ Surface provides a good grip, since it is filled with quartz</li> <li>■ Results in optimum and economical application of the decorative plaster</li> </ul>	
<b>Technical data</b>	Binder base	Silicate of potassium Acrylic-resin dispersion
	Specific gravity	approx. 1,7 g/cm <sup>3</sup>
<b>Application instructions</b>	Preparation	<ul style="list-style-type: none"> <li>- Carefully cover glass, ceramics, brick slip, natural stone, varnished and anodized surfaces.</li> <li>- Remove splashes immediately with water.</li> </ul>
	Substrate pre-treatment	<ul style="list-style-type: none"> <li>- All substrates must be sound, even, clean and free from adhesion-reducing residue.</li> <li>- Apply Sub Primer Si to substrates that need to be stabilised.</li> </ul>
	Mixing	Ready for application Can be thinned with 3 % water max.
	Application	<ul style="list-style-type: none"> <li>- Apply by brush or roller.</li> <li>- Use short-pile rollers to ensure an even application.</li> </ul>
	Consumption	approx. 200 - 250 ml/m <sup>2</sup> Determine the exact amount of material required by coating a test area on site.
	Information about the weather	The temperature must not fall below + 8 °C during application and drying.
	Drying time	approx. 2 - 6 hours Dependent on temperature and relative humidity
	Cleaning of tools	With water while product is still fresh

<b>Packaging</b>	Article number	06123
	Packaging unit	PP tub 15 l
	Colour	Natural white and pigmented
<b>Other information</b>	Transport	Not a hazardous product
	Storage	Minimum storage life of 1/2 year if kept cool, protected against frost and in the original sealed packaging.
	Information on safety	S 2: Keep away from children S 23: Do not breathe aerosol S 24/25: Avoid contact with the skin and eyes S 29: Do not empty into drains

We will be pleased to provide the EC safety data sheet on request.