

Equalizing Finish

External wall paint for mineral and synthetic-resin bonded substrates

Areas of application	Exterior wall paint for matching the colour of pigmented mineral textured plasters.	
Product properties	<ul style="list-style-type: none"> ■ Weather-resistant ■ Highly water-vapour permeable ■ Water-repellent ■ High opacity ■ Matt ■ Wide range of design options using the alsecco-Creative-Colour-System 	
Technical data	Binder base	Acrylic-resin dispersion
	Diffusion-equivalent air-layer thickness	s_d : approx. 0,07 m to DIN 52615 Guaranteed limit: $s_d \leq 2,0$ m
	Capillary water absorption	w: approx. 0,08 kg/(m ² h ^{1/2}) to DIN 52617 Guaranteed limit: w < 0,5 kg/(m ² h ^{1/2})
	Opacity	approx. 90 %
Application instructions	Substrate pre-treatment	All substrates must be dry, sound, clean and free from adhesion-reducing residue.
	Mixing	Ready for application Can be thinned with 5 % water max.
	Application	<ul style="list-style-type: none"> - Apply a single coat by brush, roller or as spray and smooth over. - Apply wet in wet without leaving application marks. - Two coats are applied if the difference in shade between the substrate and the Equalizing Finish is greater than 10 lightness values.
	Consumption	approx. 150 - 200 ml/m ² Determine the exact amount of material required by coating a test area on site.
	Information about the weather	The temperature must not fall below + 5 °C during application and drying.
	Drying time	approx. 2 - 6 hours Dependent on temperature and relative humidity
	Cleaning of tools	With water while product is still fresh

Packaging	Article number	04087
	Packaging unit	PP tub 15 l
	Colour	White and pigmented
Other information	Transport	Not a hazardous product
	Storage	Minimum storage life of 1 year if kept cool, protected against frost and in the original sealed packaging.
	Information on safety	We will be pleased to provide the EC safety data sheet on request.